Manual call point BF-502/EX

Part No.	116-BF-502/EX
Manufacturer	Autronica Fire and Security AS
Model	BF-502/EX



Summary

Manual call point with break glass for use in harsh environmental conditions. For use in hazardous area zone 0, 1 or 2. The call point must be connected to the approved EX barrier BZ-500.

Specifications

Addressing	Automatic
Cable Entries	2 x M20
Classification Societies Design (per manufacturer datasheet)	Designed to meet the requirement of the major maritime classification societies
Colour	Red
Datasheet Document	Doc-1000116-4, 2026-09-18
Degree of Protection	IP66 & IP67 (with approved cable glands and/or plugs of minimum the same IP level)
Dimensions	93 x 93 x 62 mm (H x W x D)
Environmental Requirement	EN 54
Ex Type Examination Certificate (per manufacturer datasheet)	NEMKO 03ATEX218X
Hazardous Area (per manufacturer datasheet)	Zone 0, 1, 2, 20, 21 or 22
IECEx Certificate (per manufacturer datasheet)	NEM 11.0009X
Maintenance	Replace broken glass
Material	Glass reinforced polyester (GRP)
Notified Body (per manufacturer datasheet)	Nemko ID No. 0470
Operating Temperature	-20 to +70 °C
Short Circuit Isolator	In each unit
Standby Current	0.3 mA
Storage Temperature	-55 to +70 °C
Voltage	10 to 27 V DC
Weight	0.5 kg

sales@maxonemarine.com