Manual call point BF-506/EX

Part No.	116-BF-506/EX
Manufacturer	Autronica Fire and Security AS
Model	BF-506/EX



Summary

Manual call point with break glass in aluminium housing. For use in hazardous area zone 0, 1 or 2. It must be connected to the approved EX barrier BZ-500.

Specifications

Addressing	Automatic
Cable Entries	2 x M20 (top) and 1 x M20 (side); back box can be rotated to give 2 bottom and 1 side entries
Colour	Red
Datasheet Document	116-P-BF506EX/CGB, Rev. A, 2020-01-21
Degree of Protection	IP66 (with IP66 approved cable glands and/or plugs)
Environmental Requirement	EN 54
Ex Type Examination Certificate (per manufacturer datasheet)	NEMKO 03ATEX218X
Hazardous Area (per manufacturer datasheet)	Zone 0, 1 or 2
IECEx Certificate (per manufacturer datasheet)	NEM 11.0009X
Maintenance	Replace broken glass
Material	Marine grade copper free LM6 aluminium with stainless steel lift flap
Notified Body (per manufacturer datasheet)	Nemko ID No. 0470
Operating Temperature	-20 to +70 °C
Short Circuit Isolator	In each unit
Standby Current	0.3 mA
Storage Temperature	-55 to +70 °C
Voltage	10 to 27 V DC
Weight	0.8 kg

sales@maxonemarine.com