Manual call point BF-510WP-H

Part No.	116-BF-510WP-H
Manufacturer	Autronica Fire and Security AS
Model	BF-510WP-H



Summary
Manual call point with break glass for outdoor use. High current. The high IP degree of the enclosure makes the call point suitable for outdoor applications.

Specifications

Addressing	Automatic
Alarm Current	6 mA
CPD Certificate (per manufacturer datasheet)	0333-CPD-075245
Cable Entries	3 x M20 (back box knockouts: two top, one bottom)
Classification Societies Design (per manufacturer datasheet)	Designed to meet the requirement of the major maritime classification societies
Colour	Red
Datasheet Document	Doc-1000330-5, 2026-05-28
Degree of Protection	IP66 with cover
Degree of Protection (no cover)	IP52 without cover
EN 54-11 / EN 54-17 (per manufacturer datasheet)	Approved according to EN 54-11 and EN 54-17
Environmental Requirement	EN 54
Maintenance	Replace broken glass
Material	ABS
Maximum Loop Current	400 mA
Operating Temperature	-40 to +70 °C
Response Time	Maximum 3 seconds
Short Circuit Isolator	In each unit
Standby Current	0.3 mA
Storage Temperature	-55 to +70 °C
Voltage	16 to 26 V DC
Weight	200 g

sales@maxonemarine.com