Consilium ST450EC CO LHS Gas Detector (1228004/500/LHS)

Product reference	
Part No.	1228004/500/LHS
Manufacturer	Consilium
Model	ST450EC-CO



Product overview

Consilium ST450EC international-standard carbon monoxide detector with a 0-500 ppm LHS measuring range. The manufacturer ordering table identifies this exact SKU, gas, range and operating conditions; it does not establish stock, current certificate validity, supplied configuration, delivered calibration or site-specific installation compatibility. Before ordering, confirm gas, range, calibration, complete ordering configuration, system compatibility, installation requirements, supplied items and included components, and stock.

Technical specifications

Model designation	ST450EC-CO	Signal cable (standard)	2-wire shielded, 0.75 … 2.5 mm2 (excluding earth connection and Modbus)
Order code	1228004/500/LHS	Signal cable (remote)	4-wire shielded, 0.75 … 2.5 mm2 (excluding earth connection and Modbus)
Gas type	CO	Cable gland	Standard Brass, optional SS (thread M20x1.5)
Measuring range (CO)	0-500 ppm (LHS)	Load impedance	max. 160 Ω at 24 VDC
Operating temperature	-30 to +50 °C	Pressure range	Toxic: Atmospheric ± 10%, Oxygen: 80 to 120 kPa
Relative humidity (N.C.)	15-90%	Enclosure material	Coated aluminum or SS
Ordering condition footnotes	* Acc. EN 50104: -10 to +50ºC / 20 to 90 r.H. N.C **Acc. EN IEC 62990-1: -25 to +55 °C / 20 to 90 % r.H. N.C	Dimensions	179 x 189 x 107 mm (HxWxD)
Sensor type	Electrochemical sensor (2 or 3 electrodes)	Weight	1.8 kg (Alu), 3.15 kg (SS)
Display	Digital graphic display with backlight	Ingress protection	IP 66 (Sensor IP 6x)*
Status LED display	Green: OK, Red: Alarm, Yellow: SF (System Failure), Blue: User menu active	Enclosure gas sensor	SS 316
Power supply	24-28 VDC (max. 40 mA)(120 mA remote)	IP rating footnote	* IP ratings do not imply that the equipment will detect gas during and after exposure to those conditions.
Outputs	Analogue: 4-20 mA (<2.4 mA system failure, >20 mA overrange) Digital: RS485 Modbus RTU (half-duplex)		