# IC10 Address Unit

| Product reference | |
|---|---|
| Part No. | 5200272-00A |
| Manufacturer | Consilium / Salwico |
| Model | IC10 |




sales@maxonemarine.com

## Key product facts

01 · Ingress protection
IP22

## Product overview

The IC10 is an address unit for fire alarm systems.

## Key features

- It has been designed for use in dry spaces.

## Technical specifications

| | | | |
|---|---|---|---|
| Manufacturer Article Number | 5200272-00A | Ingress protection | IP22 |
| System | TS1000 | Relative humidity | 95% at low temperature; 93% ± 3% at high temperature |
| Loop nominal voltage | 35 VDC | Ambient temperature | -40 °C to +70 °C |
| Loop working voltage | 22–38 VDC | Cable terminals | 2.5 mm² |
| Loop working current | 0.2 mA | Material | PC/ABS |
| Minimum sub loop voltage | 19 VDC nominal | Colour | NCS-0502Y |
| Output current limit | 5 or 15 mA | Weight | 90 g |
| Output function | Pulsed or steady | AE-2-E replacement restriction | IC10 replaces AE-2-E only without external 24 VDC; applicable replacement PCB casing must be discarded. |
| End of line | Not included | Device type and switch settings | Use original Table 2 to set device type with SW2 DIP 1-5; DIP 8 always ON; DIP 7 normally OFF; high-current mode only when necessary. |